

Contrastive Language–Image Pre-training for the Italian Language

Federico Bianchi
Bocconi University
Milan, Italy
f.bianchi@unibocconi.it

Giuseppe Attanasio
Politecnico di Torino
Turin, Italy
giuseppe.attanasio@polito.it

Raphael Pisoni
Independent Researcher
Vienna, Austria
raphael.pisoni@gmail.com

Silvia Terragni
University of Milano-Bicocca
Milan, Italy
s.terragni4@campus.unimib.it

Gabriele Sarti
University of Groningen
Groningen, The Netherlands
g.sarti@rug.nl

Sri Lakshmi
Independent Researcher
Chennai, India
srilakshmiimhskalirs@gmail.com

Abstract

CLIP (Contrastive Language–Image Pre-training) is a very recent multi-modal model that jointly learns representations of images and texts. The model is trained on a massive amount of English data and shows impressive performance on zero-shot classification tasks. Training the same model on a different language is not trivial, since data in other languages might be not enough and the model needs high-quality translations of the texts to guarantee a good performance. In this paper, we present the first CLIP model for the Italian Language (CLIP-Italian), trained on more than 1.4 million image-text pairs. Results show that CLIP-Italian outperforms the multilingual CLIP model on the tasks of image retrieval and zero-shot classification.

1 Introduction

The recent interest in combining different kinds of source domains to incorporate broader context in the training process has led to a surge in multi-modal models spanning modalities like text and vision (Radford et al., 2021) or text and speech (Schneider et al., 2019). A multi-modal architecture learns by jointly optimizing its state and parameters on two or more input domains (e.g., images, texts, tabular data, audio signals), with a cost function that may vary depending on the task.

Contrastive Language–Image Pre-training (CLIP) (Radford et al., 2021) is among the most recent multi-modal models for joint learning representations of image and text. The neural network proposed by OpenAI learns to pair visual concepts to their description in natural language

by leveraging a contrastive loss that pushes images and their respective captions closer in the embedding space. CLIP is thus trained on a large-scale dataset composed of images and their corresponding captions. The dataset used in this context contains 400 million images collected on the web.

Although the model shows impressive zero-shot performance at many supervised tasks, its capabilities are bounded to the language on which the model is trained, i.e. the English language. Although there have been efforts to introduce multilingual CLIP models,¹ it is well-known that multilingual models tend not to perform as well as language-specific ones (Nozza et al., 2020).

We thus propose to fine-tune a specialized version of CLIP on a language different than English, i.e. Italian. Indeed, in this paper, we describe CLIP-Italian², a model we developed during the Hugging Face Community Week.³ In the spirit of transparency, we release our best performing model⁴ along with all the produced material. Appendix A provides additional details on such releases.

Contributions. We combine different data sources to generate the largest publicly available

¹<https://huggingface.co/sentence-transformers/clip-ViT-B-32-multilingual-v1>

²The choice of Italian comes from the nationality of some of the authors. However, the approach presented in this paper can be generalized to other language and domain text-image pairs without loss of generality.

³<https://discuss.huggingface.co/t/open-to-the-community-community-week-using-jax-flax-f7104>

⁴<https://huggingface.co/clip-italian/clip-italian>

multi-modal dataset for the Italian language, with 1.4M image-caption pairs. We use this dataset to train and release the first CLIP image-text model for the Italian language. Moreover, we provide an online demo that can be used to test the model’s capabilities. Finally, we show that this model performs better than its multi-lingual counterpart in two well-established multi-modal tasks, namely image retrieval and zero-shot image classification.

2 Contrastive Language–Image Pre-training

The task on which CLIP is trained is as follows: given an image in input, the model has to predict which of the different texts is the correct element to associate with the input image. Although it is not mandatory, the correct element typically contains a textual description of the content of the image. In this way, the model learns to associate visual concepts and their respective natural language description.

CLIP’s architecture consists of two distinct encoders, one for images and one for texts. The two encoders share the same embedding space. At training time, all the images and texts of a given mini-batch are projected to a 512 dimensional space. Next, vector similarities are computed for each pair of image and text embeddings and cross entropy loss is applied. The average loss along the image and text dimensions is the final contrastive loss.

Figure 1 briefly summarizes the training process and the loss employed by CLIP to learn the representations.

After training, CLIP can be used for a variety of different tasks: since it embeds image and text in the same space it is possible to tackle image retrieval and zero-shot classification of images by looking at the similarities between texts and images.

Our version of CLIP differs from the original. Mainly, we do not pre-train the encoders from scratch but we start from previous checkpoints for both the vision and the text components. The advantage of this approach is that we use models that are already tuned and we just need to apply a language-specific fine-tuning of the components to create CLIP-Italian. We extensively cover training details in Section 4.

3 Datasets

We hereby describe the four different sources of data we have used to train our CLIP-Italian model.

- WIT (Srinivasan et al., 2021) is an image-caption dataset collected from Wikipedia. It is a multilingual dataset, but we pre-processed and extracted the Italian subset. For each image, there are different possible captions. In this work we focused on the Reference Description captions, as they were described in the paper as the most topical and highest quality captions.
- MSCOCO-IT (Scaiella et al., 2019).⁵ The captions of this image-caption dataset come from the original MSCOCO dataset (Lin et al., 2014) and translated with Microsoft Translator. The 2017 version of the MSCOCO training set contains more than 100K images. More than one caption is available for each image.
- Conceptual Captions (CC) (Sharma et al., 2018).⁶ In this dataset, there are more than 3 millions image-caption pairs, collected from the web. We downloaded the images with the URLs provided by the dataset, but some of them were not available. Eventually, we translated approximately 710K captions to Italian using DeepL.⁷
- La Foto del Giorno (ILPOST).⁸ This image-caption dataset is collected from *Il Post*, a prominent Italian online newspaper. Starting from early 2011, every day, the editors at *Il Post* have been selecting several images picturing the most salient events in the world. Each photo comes along with an Italian caption. The resulting collection contains almost 30K pairs of images-captions.

3.1 Translations

Instead of relying on open-source translators, we use DeepL, which provides high-quality translations. This decision is related to the low amount

⁵<https://github.com/crux82/mscoco-it>

⁶<https://github.com/google-research-datasets/conceptual-captions>

⁷<https://www.deepl.com/>

⁸<https://www.ilpost.it/foto-del-giorno/>

```

# using BERT and ViT to get encode the images
encoded_images = image_encoder(images)
encoded_texts = text_encoder(texts)
logit_scale = 20

# using the projections
embedded_images = l2_normalization(image_projection(encoded_images))
embedded_texts = l2_normalization(text_projection(encoded_texts))

logits = np.dot(embedded_images, embedded_text.T) * logit_scale

labels = np.arange(n) # correct image-text match is on the diagonal
loss_images = cross_entropy_loss(logits, labels, axis=0)
loss_texts = cross_entropy_loss(logits, labels, axis=1)
loss = (loss_images + loss_texts)/2

```

Figure 1: Numpy-like pseudo code that describes the CLIP loss, image is inspired to the one provided by (Radford et al., 2021).

Dataset	Captions
WIT	525,950
MSCOCO-IT	116,195
CC	712,890
ILPOST	29,055

Table 1: The number of captions collected per dataset.

of available images (with respect to the original work of OpenAI). We wanted to avoid the risk of polluting the available data, however, we are aware of the bias (e.g., gender and age) that translation systems introduce during translations (Hovy et al., 2020).

We translated 700K captions and we evaluated their quality. Some of the captions are available in Figure 2.

To assess the quality of the translations, three of the authors (native Italian speakers) inspected a sample of 100 of the Italian translations, comparing them with the original English caption. They rated them with scores from 1 to 4. The meaning of the value is the following: 1, the sentence has lost its meaning, or it is not possible to understand it; 2, it is possible to get the idea but there is something wrong; 3, good, however, a native speaker might complain about some translations; 4, very good translation.

The average score was 3.78 suggesting that the translations were good on average. We also computed an inter-rater agreement with Gwet’s AC1 using ordinal weighting obtaining a value of 0.858, suggesting a strong agreement between the annotators.

3.2 Data Cleaning

Many of the captions in WIT describe ontological knowledge and encyclopedic facts (e.g., “Roberto Baggio in 1994”). These kinds of texts are not useful to learn a good mapping between images and captions if additional information is not provided. To prevent polluting the data with captions that are not meaningful, we used Part-Of-Speech (POS) tagging on the text and removed all the captions that were composed for the 80% or more by the tag PROP, i.e. proper noun, (around 10% of the total captions for WIT). This simple solution allowed us to retain much of the dataset, without introducing noise. Captions like “Dora Riparia”, “Anna Maria Mozzoni”, “Joey Ramone Place”, “Kim Rhodes”, “Ralph George Hawtrey” which are proper nouns (PROP) have been removed.

Regarding the dataset ILPOST, we used `langdetect`⁹ on its captions to remove non-Italian ones. Less than 2% of captions got lost by this filter.

4 Training

Our CLIP-Italian model is based on previous pre-trained state-of-the-art models for both the vision and textual part: we use Vision Transformer (ViT) (Dosovitskiy et al., 2021) and BERT (Devlin et al., 2019). We limited the sequence length to a maximum of 96 tokens. We use a batch size of 128. For the optimization, we used AdaBelief (Zhuang et al., 2020) with Adaptive Gradient Clipping (AGC) and a Cosine Annealing Schedule (Loshchilov and Hutter, 2017).

⁹<https://github.com/Mimino666/langdetect>

English Caption	Italian Caption
an endless cargo of tanks on a train pulled down tracks in an empty dry landscape	un carico infinito di carri armati su un treno trascinato lungo i binari in un paesaggio secco e vuoto
person walking down the aisle	persona che cammina lungo la navata
popular rides at night at the county fair	giostre popolari di notte alla fiera della contea

Table 2: Translated captions from the Conceptual Captions dataset.

We applied augmentations to the images: we used random affine transformations and perspective changes, as well as occasional equalization and random changes to brightness, contrast, saturation, and hue. We made sure to keep hue augmentations limited to give the model the ability to learn color definitions.

Since we started from pre-trained checkpoints for both the vision and the text part, we found it useful to warm-up projection layers. To do so, we first train with both the vision and text encoder frozen until loss convergence. Then, we unfroze the rest of the model to fine-tune the entire architecture. We always pick the model that has the best evaluation loss, evaluating every 15 epochs.

The text encoder we use is the Italian BERT model¹⁰ while for the vision encoder we use the pre-trained checkpoint provided by OpenAI.¹¹ Note that the OpenAI’s vision transformer differs only for a few modifications from the original ViT.

Both images and texts are then projected to 512-dimensional vectors to which we apply the loss defined in CLIP using logit scaling equal to 20. We empirically observed that the logit scaling has a strong positive impact on performance of the model.

5 Quantitative Evaluation

To the best of our knowledge, CLIP-Italian is the first model of its kind. Hence, to provide meaningful comparisons, we use the multilingual CLIP model. This model was obtained through the use of multilingual knowledge distillation (Reimers and Gurevych, 2020).

5.1 Image Retrieval

In the Image Retrieval task, we evaluate how well the images and their respective captions are

¹⁰<https://huggingface.co/dbmdz/bert-base-italian-xxl-cased>

¹¹<https://huggingface.co/openai/clip-vit-base-patch32>

Measure	CLIP-Italian	mCLIP
MRR@1	0.3797	0.2874
MRR@5	0.5039	0.3957
MRR@10	0.5204	0.4129

Table 3: Results on MSCOCO image retrieval task

mapped closely in the vector space. Given a caption, the task is to find the correct image that matches the caption from a set of images. This can be done by mapping a caption into the joint vector space and selecting the most similar image to it. We use the MSCOCO-IT validation dataset (that we have not used in the training set). The dataset contains 2000 images associated with their respective captions.

Table 3 presents the results for the image retrieval task.

5.2 Zero-shot Classification

The zero-shot image classification task replicates the experiment run by Radford et al. (2021) on ImageNet. To do this, we used DeepL to automatically translate the image labels in ImageNet. We prepend all the labels in the test set with the article and translate them (*a cat* is translated into “un gatto”). The generated labels are then prepended with the text “una foto di” (a photo of) as in “una foto di un gatto” (a photo of a cat) to have the final prompt. Note that this is a much lighter prompt engineering than the one in Radford et al. (2021) where different prompt templates are computed and averaged. Given an input image and the so-generated prompts, we generate the embeddings (both for the image and all the prompts) and compute the similarities. We expect the correct label of the image to be the closest prompt in the embedding space. We compute accuracy metrics on these results.

Table 4 presents the results for the zero-shot classification task.

Measure	CLIP-Italian	mCLIP
Accuracy@1	22.11	20.15
Accuracy@5	43.69	36.75
Accuracy@10	52.55	42.91

Table 4: Results on ImageNet-1000 classification task

5.3 Discussion

Our results confirm that CLIP-Italian is very competitive and outperforms mCLIP on the two different tasks we have been testing. Note that our results for zero-shot ImageNet classification of the CLIP-Italian model (trained on 1.4 million image-text pairs) are lower than those shown in Radford et al. (2021) (trained on 400 million image-text pairs). However, considering that our results are in line with those obtained by mCLIP, we think that the translated image labels most probably had an impact on the final scores. Even with limited data sources, training time, and computational resources (two weeks of Google Cloud TPU sponsorship), the results obtained largely improve the state of the art in multi-modal image-text tasks for the Italian language.

6 Qualitative Evaluation

Thanks to the support by HuggingFace, we are also able to provide an online demo that can be used to experiment with our model.¹²

We show some examples related to the image retrieval task on the Unsplash25K dataset.¹³ Figure 2 shows the results of the query “due cani sulla neve” (two dogs on the snow), the model correctly finds the image, combining the concept of “snow” and the one of “two dogs”. The model showed moderate numeracy capabilities during empirical evaluation, identifying up to three distinct or repeated elements inside images. We associate this behavior to implicit knowledge present in the training set, as we observe a steep drop in coherence when more than three elements are present. We believe this behavior is due to the likely low number of training points depicting more than three subjects in the scene.

Figure 3 shows similar performance for “una coppia al tramonto” (a couple during sunset), where the model was able to identify two people and the

sun light in the background. A similar query, but with a mountain as a background, can be found in Figure 4.

However, the model is subject to limitations and biases. An example of a limitation is shown in Figure 5 where the query “un topolino” (a small mouse) resulted in finding an image of a small hedgehog. We also empirically found that the model shows some biases and has learned some stereotypes that need to be explored more in detail when using this model.



Figure 2: Result of the query “due cani sulla neve” (two dogs on the snow) on the Unsplash25K dataset.



Figure 3: Result of the query “una coppia al tramonto” (a couple during sunset) on the Unsplash25K dataset.

¹²<https://huggingface.co/spaces/clip-italian/clip-italian-demo>

¹³<https://github.com/unsplash/datasets>



Figure 4: Result of the query “una coppia in montagna” (a couple on the mountain) on the Unsplash25K dataset.



Figure 5: Result of the query “un topolino” (a small mouse) on the Unsplash25K dataset.

7 Conclusions

In this paper, we have presented the first CLIP model for the Italian language, trained on 1.4 million image-text pairs. The model shows promising performance in two well-established tasks, suggesting many possible future applications.

Ethical Considerations

Large scale models are difficult and costly to train (Bender et al., 2021); we computed the cost of the different experiments we ran and we estimated a total of 2,688\$ for each TPU used. This result comes from the hourly cost of the TPU (8\$) for 14 days; Note that we had access to a second TPU VM for part of the project and that in this estimate we are ignoring storage and data transfer costs. Strubell et al. (2019) describe in detail how these model can have a huge environmental impact.

As Bianchi and Hovy (2021) describe, these computational needs are quickly becoming unfeasible for many universities, and even companies can

struggle when applying large models on datasets, as also described by Bianchi et al. (2021).

Acknowledgments

This work was only possible thanks to the Hugging Face and Google teams that provided two TPUs to train the CLIP-Italian model. Federico Bianchi is a member of the Bocconi Institute for Data Science and Analytics (BIDSA) and the Data and Marketing Insights (DMI) unit.

References

- Emily M Bender, Timnit Gebru, Angelina McMillan-Major, and Shmargaret Shmitchell. 2021. On the dangers of stochastic parrots: Can language models be too big? In *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, pages 610–623.
- Federico Bianchi and Dirk Hovy. 2021. [On the gap between adoption and understanding in NLP](#). In *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pages 3895–3901, Online. Association for Computational Linguistics.
- Federico Bianchi, Bingqing Yu, and Jacopo Tagliabue. 2021. [BERT goes shopping: Comparing distributional models for product representations](#). In *Proceedings of The 4th Workshop on e-Commerce and NLP*, pages 1–12, Online. Association for Computational Linguistics.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. [BERT: Pre-training of deep bidirectional transformers for language understanding](#). In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. 2021. [An image is worth 16x16 words: Transformers for image recognition at scale](#). In *International Conference on Learning Representations*.
- Dirk Hovy, Federico Bianchi, and Tommaso Fornaciari. 2020. [“you sound just like your father” commercial machine translation systems include stylistic biases](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 1686–1690, Online. Association for Computational Linguistics.
- Tsung-Yi Lin, Michael Maire, Serge Belongie, James Hays, Pietro Perona, Deva Ramanan, Piotr Dollár,

- and C Lawrence Zitnick. 2014. Microsoft coco: Common objects in context. In *European conference on computer vision*, pages 740–755. Springer.
- Ilya Loshchilov and Frank Hutter. 2017. [SGDR: stochastic gradient descent with warm restarts](#). In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*. OpenReview.net.
- Debora Nozza, Federico Bianchi, and Dirk Hovy. 2020. What the MASK? making sense of language-specific bert models. *arXiv preprint arXiv:2003.02912*.
- Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. 2021. [Learning transferable visual models from natural language supervision](#). In *Proceedings of the 38th International Conference on Machine Learning, ICML 2021, 18-24 July 2021, Virtual Event*, volume 139 of *Proceedings of Machine Learning Research*, pages 8748–8763. PMLR.
- Nils Reimers and Iryna Gurevych. 2020. [Making monolingual sentence embeddings multilingual using knowledge distillation](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 4512–4525, Online. Association for Computational Linguistics.
- Antonio Scaiella, Danilo Croce, and Roberto Basili. 2019. Large scale datasets for image and video captioning in italian. *IJCoL. Italian Journal of Computational Linguistics*, 5(5-2):49–60.
- Steffen Schneider, Alexei Baevski, Ronan Collobert, and Michael Auli. 2019. wav2vec: Unsupervised pre-training for speech recognition. In *INTER-SPEECH*.
- Piyush Sharma, Nan Ding, Sebastian Goodman, and Radu Soricut. 2018. [Conceptual captions: A cleaned, hypernymed, image alt-text dataset for automatic image captioning](#). In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2556–2565, Melbourne, Australia. Association for Computational Linguistics.
- Krishna Srinivasan, Karthik Raman, Jiecao Chen, Michael Bendersky, and Marc Najork. 2021. Wit: Wikipedia-based image text dataset for multimodal multilingual machine learning. *arXiv preprint arXiv:2103.01913*.
- Emma Strubell, Ananya Ganesh, and Andrew McCalum. 2019. [Energy and policy considerations for deep learning in NLP](#). In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 3645–3650, Florence, Italy. Association for Computational Linguistics.
- Juntang Zhuang, Tommy Tang, Yifan Ding, Sekhar Tatikonda, Nicha Dvornek, Xenophon Papademetris, and James S Duncan. 2020. Adabelief optimizer: Adapting stepsizes by the belief in observed gradients. *arXiv preprint arXiv:2010.07468*.

A Material Released

For the best transparency, and to allow further development upon our work, we release the pre-trained model,¹⁴ the modeling and training code,¹⁵ a CometML report with training logs and metrics,¹⁶

Interested readers can directly test CLIP-Italian’s capabilities at our official demo.¹⁷

¹⁴<https://huggingface.co/clip-italian/clip-italian>

¹⁵<https://github.com/clip-italian/clip-italian>

¹⁶<https://www.comet.ml/g8a9/clip-italian/reports/clip-italian-training-metrics>

¹⁷<https://huggingface.co/spaces/clip-italian/clip-italian-demo>