

Few-Shot Self-Rationalization with Natural Language Prompts

Ana Marasović* Iz Beltagy* Doug Downey Matthew E. Peters

Allen Institute for Artificial Intelligence, Seattle, WA, USA
 {anam,beltagy,doug,d,matthewp}@allenai.org

Abstract

Self-rationalization models that predict task labels and generate free-text elaborations for their predictions could enable more intuitive interaction with NLP systems. These models are, however, currently trained with a large amount of human-written free-text explanations for each task which hinders their broader usage. We propose to study a more realistic setting of self-rationalization using few training examples. We present FEB—a standardized collection of four existing English-language datasets and associated metrics. We identify the right prompting approach by extensively exploring natural language prompts on FEB. Then, by using this prompt and scaling the model size, we demonstrate that making progress on few-shot self-rationalization is possible. We show there is still ample room for improvement in this task: the average plausibility of generated explanations assessed by human annotators is at most 51%, while plausibility of human explanations is 76%. We hope that FEB together with our proposed approach will spur the community to take on the few-shot self-rationalization challenge.

1 Introduction

Models constrained to be more understandable to people are easier to troubleshoot and more useful in practice (Rudin et al., 2021). For instance, constraining a model that answers the question “Which linguist invented the lightbulb?” with “none” to also provide the reason—“Thomas Edison is the inventor of the lightbulb and he was not a linguist”—makes the model easier to control and interact with (Kim et al., 2021). Models that jointly predict task labels and generate *free-text explanations* for their predictions (as in the previous example) are known as *self-rationalization models* (Wiegrefe et al., 2021). Their explanations are arguably more faithful and stable than post-hoc explanations since

they are intrinsic to the model (Melis and Jaakkola, 2018). The free-text format is essential for explaining tasks requiring reasoning about unstated knowledge such as commonsense (Marasović et al., 2020), and it makes explanations more intuitive to people compared to highlights of individual words (Camburu et al., 2018). Despite these benefits, self-rationalization models are not widely used, in part because their training currently requires an abundance of human-authored explanations for each task (Narang et al., 2020). A possible solution is few-shot learning, which has shown promising results in recent years. To help the research community begin tackling self-rationalization with only a few examples, we present (i) FEB—a standardized collection of four existing English-language datasets and associated metrics, and (ii) the first approach for the task established through an extensive evaluation of natural language prompts.¹

One approach to few-shot learning is *prompt-based finetuning* with *natural language prompts*. Such prompts are produced by formatting finetuning instances using a format similar to that used in pretraining, based on the idea that finetuning examples that look similar to pretraining ones will be more informative in the fewshot setting. A few prompts are then used for finetuning. In this paper, we explore whether prompt-based finetuning can be extended to induce few-shot self-rationalization behavior in addition to few-shot prediction. To measure our progress, we first introduce FEB as benchmark dataset consisting of human authored free-text explanations across four distinct end tasks including natural language inference and commonsense tasks (§2). Since finding appropriate prompts is often challenging (Gao et al., 2021), we then extensively explored natural language prompts for few-shot self-rationalization. In our experiments, we fine-tune the T5 and UNIFIEDQA pretrained encoder-decoder transformers (Raffel et al., 2020;

*Equal contributions.

¹Few Explanations Benchmark (FEB)

FEB Tasks		# Shots	Similar T5 Pretraining Tasks	
E-SNLI (Camburu et al., 2018)	Classify the entailment relation between two sequences	16	MNLI (Williams et al., 2018)	Classify the entailment relation between two sequences
ECQA (Aggarwal et al., 2021)	Answer a question, given five answer choices	48	RECORD (Zhang et al., 2018)	Answer a cloze-style query about a passage given entities in it
COMVE (Wang et al., 2019b)	Select one of two sequences as more nonsensical	24	COPA (Roemmele et al., 2011)	Select one of two sequences as the cause/effect of a premise
SBIC (Sap et al., 2020)	Classify a post as offensive or not	24	COLA (Warstadt et al., 2019)	Classify a sentence as acceptable or not

Table 1: The left part of the table shows tasks that we have included in FEB. Tasks on the right are included in T5’s pretraining and they are similar to FEB’s tasks. We explore self-rationalization prompts for FEB’s tasks based on the tasks on the right, and compare them to prompts designed as span infilling and QA (§3).

Khoshabi et al., 2020), and show that versatile question-answering prompts (defined in §3.1) outperform prompts based on span infilling by 8.73 accuracy points, as well as prompts designed by following the most similar T5’s supervised pretraining task by 3.21.

We then study the impact of model size on few-shot self-rationalization to investigate whether the quality of generated explanations scales with the size as good as the accuracy of predicting task labels. To this end, we also evaluate self-rationalization behavior of GPT-3 (Brown et al., 2020). Our experiments show that explanation plausibility scored by human annotators and end task model performance improve with increasing model size, despite models being overparametrized. Specifically, the difference in plausibility scores between the BASE and 3B model versions ranges from [6.24, 24.85] (on average 14.85). The average plausibility score across datasets is 43.36 (UNIFIEDQA-3B) and 50.58 (GPT-3). While encouraging, our results show that there is still a large gap between model and human performance (25.75 for GPT-3), and we hope this work will help enable the research community to take on the few-shot self-rationalization challenge.

Our code for producing data splits, prompt construction, and model training/evaluation, as well as human evaluation templates are publicly available.²

2 FEB Benchmark

There has been an explosion of interest in generating free-text explanations and in few-shot learning in the last 1–2 years. However, appropriate datasets and metrics for few-shot self-rationalization have not yet been established. We thus introduce

the FEB benchmark—a suite of existing English-language datasets with human-authored free-text explanations and associated metrics for few-shot self-rationalization. We expect that FEB will simplify future model comparison and lower barriers to entry for those interested in working on this task.

Datasets in FEB To identify available datasets suitable for few-shot self-rationalization, we start with a recent overview of datasets with free-text explanations (Wiegrefe and Marasović, 2021) and filter them according to the following criteria: (i) the input is textual, (ii) the explanation consists of one sentence or 2-3 simple sentences, (iii) the task has a fixed set of possible labels, (iv) the explanation is human-authored, and (v) the dataset has at least 389 instances.³ We use the second and third criteria to narrow the scope to easier self-rationalization since we expect that few-shot self-rationalization is very challenging. The last requirement is introduced because we need 48 training and 350 evaluation examples.

This gives us five datasets, four of which are included in FEB and overviewed on the left in Table 1. These datasets span four different tasks: natural language inference, multiple-choice commonsense QA, nonsensical sentence selection, and offensiveness classification. We exclude CoS-E (Rajani et al., 2019) since it is reported to be too noisy to be useful for modeling and evaluating self-rationalization (Narang et al., 2021).⁴

The ECQA dataset contains not only justifications of the correct answer choice, but also justi-

³We thus exclude more complex LIAR-PLUS (Alhindi et al., 2018) and PUBHEALTH (Kotonya and Toni, 2020), and solving algebraic word problems (Ling et al., 2017).

⁴This decision might be deemed unjustified to some since CoS-E is still actively used. We thus report CoS-E results in Tables 9–10 in the Appendix, but we do not support using CoS-E in the future, especially since ECQA is introduced.

²<https://github.com/allenai/feb>

fications that refute the incorrect answer choices. We use only the former since they answer “why is [input] assigned [label]?”, just as explanations in other datasets that we have included in FEB. The SBIC dataset contains annotations of frames representing the biases and offensiveness that are implied in language. We format these frames as a self-rationalization task as follows. We allow only two labels: “offensive” and “not offensive”. If a post is not offensive, we assign it the explanation: “*This post does not imply anything offensive.*” A post can be offensive because it targets an individual or a demographic group that holds less societal power. In the former cases, a post is assigned the explanation: “*This post is a personal attack.*” Otherwise, we define a set of rules to transform SBIC annotations of which identity-based group is targeted and what stereotypes of this group are referenced or implied into a single, coherent sentence; e.g., group: *women*, stereotype: *can’t drive* → “*This post is offensive because it implies that women can’t drive*”.

To the best of our knowledge, this is the most comprehensive collection of textual self-rationalization tasks that could also be used even when working in a high-resource setting.

Automatic Evaluation Evaluating self-rationalization (predicting task labels and generating explanations for the predictions) requires end-task evaluation and assessing the explanation plausibility. We use accuracy as our end-task evaluation metric. Explanation plausibility may be described as a subjective satisfaction with how a given explanation justifies a label/answer (Yang et al., 2019). Kayser et al. (2021) present the largest currently available study on the correlation of 10 NLG metrics with human judgments of free-text explanation plausibility and report that BERTscore (Zhang et al., 2020) is most correlated (although the correlation is still weak). Thus, we use BERTscore to evaluate the similarity between gold and generated explanations. Following Kayser et al., we assign zero BERTscore for incorrectly predicted instances.⁵

We follow recent recommendations for reliable few-shot evaluation (Bragg et al., 2021). Specifically, we fix hyperparameters and use 60 random train-dev splits with 350 examples in each dev set.

⁵They say: “an explanation is expected to be false when the answer is predicted incorrectly (as it is expected to justify a wrong answer)”.

For each model, we report the mean and standard error of 60 mean accuracy/BERTscore values calculated on 60 dev sets of 350 examples.⁶ Our hyperparameters are reported in Table 8 in the Appendix. For classification tasks, the number of shots (examples per label) is chosen such that we construct a balanced training set of size 48.⁷ See Table 1 (col. 3) for exact values. For ECQA we sample 48 training examples.

Human Evaluation For our final models (§4), we conduct a human evaluation of plausibility of generated explanations following prior work (Kayser et al., 2021; Marasović et al., 2020). For each model evaluation, Kayser et al. (2021) take the first 300 dev examples that are correctly predicted by the model. This means that the dev set subsets used for human evaluation differ across models that are evaluated. However, the overlap between the evaluation sets is maximized by fixing the order of dev instances and taking the first 300.

Prior work used a single train-dev split, while FEB has 60 train-dev splits. Multiple splits provides the opportunity to account for the variance caused by changing the random seed to produce a reliable estimate of plausibility of explanations produced with only a few examples. Therefore, we take the first 6 correctly predicted examples per train-dev split which gives $6 \times 60 = 360$ total instances. Moreover, for classification tasks, we propose to take the first $6/\#\text{labels}$ correctly-predicted examples per label to have a balanced evaluation set.

Following Kayser et al. (2021), we conduct the human evaluation in two steps:

- **Step1:** Select the correct label/answer.
- **Step2:** Assess whether two explanations (gold and generated) justify the label/answer above.

The first step makes sure the annotators understood the task correctly and they are not able to submit their annotations if the answers are wrong. Ground-truth explanations are evaluated to implicitly influence annotators with a gold reference point when they evaluate generated explanations, and to measure the quality of explanation datasets. To evaluate explanations, annotators are asked “Does the

⁶To calculate the standard error for accuracy/BERTscore we use $n = 60$. The training (and likewise, dev) sets across splits can overlap, so this error reflects the variability expected in average scores when repeating our experiment with 60 new random splits of the same data sets.

⁷In early studies, we found that 48 gives models that are at least slightly above the random baseline across all four tasks.

explanation justify the answer?” and given the options {“yes”, “weak yes”, “weak no”, “no”}. These options are mapped to plausibility scores of $\{1, \frac{2}{3}, \frac{1}{3}, 0\}$, respectively. For each of the 360 examples, we calculate the mean plausibility score of 3 annotators and report the mean and the standard error of 360 mean scores. We also report the inter-annotator agreement calculated with Fleiss’ kappa. Finally, models are evaluated independently to avoid penalizing worse performing models in the presence of explanations generated by a better model.

3 Prompting for Self-Rationalization

We approach few-shot self-rationalization with prompt-based finetuning using natural language (NL) prompts. The key idea behind NL prompts is that a pretrained language model (LM) is already well-positioned to solve the end-task if we format finetuning end-task examples as similar as possible to the format used in pretraining. Following that principle, in this section, we describe our prompting approach with T5 (Raffel et al., 2020) and comprehensively evaluate three distinct prompt types with FEB. Our results show that a unified question-answering prompt combined with a T5 variant that includes additional supervised multi-task QA training (UNIFIEDQA; Khashabi et al., 2020) performs the best overall across tasks, when compared to three different alternative prompts as described below.

Self-rationalization models (Narang et al., 2020; Wiegrefe et al., 2021) are currently based on T5 for at least two reasons. First, T5 has been pretrained with many supervised tasks including classification and generation tasks, and self-rationalization involves both classification and generation. Second, T5 is one of the largest *open-sourced* pretrained models, and higher LM performance is correlated with larger model size (Kaplan et al., 2020). Therefore, all of our experiments are based on T5 (and the UNIFIEDQA variant when evaluating prompts based on a QA format). In this section, all results are obtained with the base version of these models and in §4 we scale model size.

When a LM is pretrained with only masked language modeling (Devlin et al., 2019), an appropriate NL prompt is constructed by adding and infilling masked tokens (Jiang et al., 2020). T5, however, has been pretrained with span infilling and a suite of supervised tasks whose instances

were formatted in various ways. One of these supervised tasks includes SQUAD 1.1 (Rajpurkar et al., 2016) which allows us to experiment with prompts based on QA templates. As a result, we were able to design several different types of NL prompts for T5 consistent with different aspects of its pretraining:

1. QA prompts (SQUAD_{T5}, QA_{SIMPLE}).
2. span-filling prompts (INFILLING),
3. prompts designed by following the formatting of the most similar T5’s pretraining task (\approx T5; see Table 1),

We illustrate these prompt types for COMVE in Table 2.⁸ The following sections describe these formats in detail and compare their performance using FEB.

3.1 QA Prompts

Formatting new instances as question-answer pairs has been shown to be useful for transfer learning from a QA model (Gardner et al., 2019). We first evaluate options for a versatile QA NL prompt for self-rationalization of tasks in FEB before comparing this approach with the other two prompt types (INFILLING and \approx T5) in §3.3. As alternative QA models, we investigate two models: T5 (which has been pretrained with QA supervision from SQUAD 1.1), and UNIFIEDQA (a T5 variant described in detail below). Since UNIFIEDQA was trained on a multitask mixture of many different QA datasets, these T5 variants allow us to examine the extent to which additional QA supervision can transfer to the few-shot self-rationalization setting.

Prior work (Bragg et al., 2021) introduced UNIFEW, a model based on UNIFIEDQA, that is finetuned on a few task-specific instances posed as QA. Despite its simplicity, UNIFEW achieves competitive few-shot learning performance with strong baselines for classification tasks. However, Bragg et al.’s prompts do not cover all of our task types, e.g., selecting one sequence given two as in COMVE. Moreover, the question structure in their prompts varies.⁹

Alternatively, we propose to design QA prompts with a simple principle in mind—given a non-QA task, construct an equivalent QA task in the form of short “Is...?” or “What is...?” questions. Here,

⁸Following Hendrycks et al. (2021), we add `</s>` to the end of our QA_{SIMPLE} prompts.

⁹E.g., “Topic? \n (A) Class1 (B) Class2 (C) Class3 \n The document” and “Sentence 1 Is Sentence 2? \n (A) Yes (B) No (C) Maybe”.

Sentence1: The stove was cleaned with a cleaner. Sentence2: The stove was cleaned with a mop.
Nonsensical Sentence: Sentence2 Explanation: A mop is too large to clean the stove.
Prompt: INFILLING × BASIC
Input: explain sensemaking choice1: <i>The stove was cleaned with a cleaner.</i> choice2: <i>The stove was cleaned with a mop.</i> <extra_id_0> because <extra_id_1>
Output: <extra_id_0> choice2 <extra_id_1> <i>A mop is too large to clean the stove.</i> <extra_id_2>
Prompt: INFILLING × NATURAL SOUNDING
Input: explain sensemaking choice1: <i>The stove was cleaned with a cleaner.</i> choice2: <i>The stove was cleaned with a mop.</i> It is <extra_id_0> that choice2 is less common because <extra_id_1>
Output: <extra_id_0> True <extra_id_1> <i>A mop is too large to clean the stove.</i> <extra_id_2>
Prompt: ≈T5 × COPA
Input: explain sensemaking choice1: <i>The stove was cleaned with a cleaner.</i> choice2: <i>The stove was cleaned with a mop.</i> Less common is choice2
Output: True because <i>a mop is too large to clean the stove.</i>
Prompt: SQUAD _{T5} × YES/NO + TAGS
Input: explain sensemaking question: Is choice2 more nonsensical? context: choice1: <i>The stove was cleaned with a cleaner.</i> choice2: <i>The stove was cleaned with a mop.</i>
Output: Yes because <i>a mop is too large to clean the stove.</i>
Prompt: SQUAD _{T5} × WHAT IS...? + TAGS
Input: explain sensemaking question: What is more nonsensical? context: choice1: <i>The stove was cleaned with a cleaner.</i> choice2: <i>The stove was cleaned with a mop.</i>
Output: choice2 because <i>a mop is too large to clean the stove.</i>
Prompt: QA _{SIMPLE} × YES/NO
Input: explain is choice2 more nonsensical? \n <i>The stove was cleaned with a cleaner. The stove was cleaned with a mop.</i> </s>
Output: yes because <i>a mop is too large to clean the stove.</i>
Prompt: QA _{SIMPLE} × YES/NO + TAGS
Input: explain is choice2 more nonsensical? \n choice1: <i>The stove was cleaned with a cleaner.</i> choice2: <i>The stove was cleaned with a mop.</i> </s>
Output: yes because <i>a mop is too large to clean the stove.</i>
Prompt: QA _{SIMPLE} × YES/NO + TAGS + CHOICES
Input: explain is choice2 more nonsensical? \n (A) yes (B) no \n choice1: <i>The stove was cleaned with a cleaner.</i> choice2: <i>The stove was cleaned with a mop.</i> </s>
Output: yes because <i>a mop is too large to clean the stove.</i>
Prompt: QA _{SIMPLE} × WHAT IS...?
Input: explain what is more nonsensical? \n <i>The stove was cleaned with a cleaner. The stove was cleaned with a mop.</i> </s>
Output: choice2 because <i>a mop is too large to clean the stove.</i>
Prompt: QA _{SIMPLE} × WHAT IS...? + TAGS
Input: explain what is more nonsensical? \n choice1: <i>The stove was cleaned with a cleaner.</i> choice2: <i>The stove was cleaned with a mop.</i> </s>
Output: choice2 because <i>a mop is too large to clean the stove.</i>
Prompt: QA _{SIMPLE} × WHAT IS...? + TAGS + CHOICES
Input: explain what is more nonsensical? \n (A) choice1 (B) choice2 \n choice1: <i>The stove was cleaned with a cleaner.</i> choice2: <i>The stove was cleaned with a mop.</i> </s>
Output: choice2 because <i>a mop is too large to clean the stove.</i>

Table 2: COMVE self-rationalization prompts that we design and test. INFILLING marks span-filling prompts; ≈T5 prompts made by following the most similar T5 pretraining task (Table 1); SQUAD_{T5} prompts designed following SQUAD’s formatting in T5 pretraining; and QA_{SIMPLE} prompts made following UNIFIEDQA. This table shows variations of these prompt types. We refer to spans “choice1:”/“choice2:” as TAGS, and to “(A) yes (B) no”/“(A) choice1 (B) choice2” as CHOICES. YES/NO and WHAT IS...? refer to a question type. More info in §3.

	Prompt	Accuracy	BERTscore
E-SNLI	UNIFEW	61.68 _{0.58}	55.85 _{0.53}
	+ tags	63.61 _{0.44}	57.34 _{0.41}
	Is...?	47.47 _{0.52}	42.70 _{0.47}
	+ tags	66.59 _{0.51}	60.05 _{0.47}
	+ tags & choices	64.43 _{0.53}	58.16 _{0.49}
	What is...?	40.67 _{0.44}	36.50 _{0.40}
	+ tags	75.05 _{0.34}	67.52 _{0.33}
	+ tags & choices	69.28 _{0.68}	62.46 _{0.62}
	RANDOM BASELINE	33.33	-
	RANDOM BASELINE	20.00	-
ECQA	UNIFIEDQA	41.37 _{0.34}	36.72 _{0.30}
	Is...?	52.69 _{0.35}	47.70 _{0.31}
	+ tags	52.47 _{0.32}	47.47 _{0.30}
	+ tags & choices	52.19 _{0.33}	47.27 _{0.30}
	What is...?	50.60 _{0.22}	45.68 _{0.20}
	+ tags	67.33 _{0.71}	60.97 _{0.64}
	+ tags & choices	62.56 _{0.65}	56.68 _{0.59}
	RANDOM BASELINE	50.00	-
	UNIFEW	66.15 _{0.43}	63.84 _{0.44}
	Is...?	63.50 _{0.44}	61.21 _{0.42}
SBIC	+ tags	62.64 _{0.45}	60.43 _{0.45}
	+ tags & choices	63.63 _{0.42}	61.31 _{0.43}
	What is...?	67.35 _{0.38}	65.03 _{0.37}
	+ tags	67.55 _{0.41}	65.29 _{0.39}
	+ tags & choices	65.43 _{0.58}	63.07 _{0.59}
	RANDOM BASELINE	50.00	-

Table 3: Prompting UNIFIEDQA with with “Is...?” and “What is...?” questions, and UNIFEW’s prompts. See §3.1 for descriptions of these prompts. For ECQA we use the original UNIFIEDQA format for multiple-choice QA. We also inspect the effects of adding answer choices and *tags* (defined in §3.1) to the input.

“Is...?” questions have yes/no answers (sometimes “maybe”), and task labels verbatim are answers to “What is...?” questions (e.g., “offensive” and “not offensive”). Then, we follow the formats proposed in UNIFIEDQA: “*question* \n (A) *choice*₁ (B) *choice*₂...” and “*question* \n *paragraph*”. The output takes the form of “*answer* because *explanation*”. See Table 2 for examples of final prompts, denoted as QA_{SIMPLE} .

There are two other factors to consider. First, we need to decide whether to add answer choices to the input, given that UNIFIEDQA has been pretrained with both multiple-choice and extractive QA tasks.

	E-SNLI	ECQA	COMVE	SBIC
UNIFA	75.05 _{0.34}	41.37 _{0.34}	67.33 _{0.71}	67.55 _{0.41}
T5	77.86 _{0.34}	36.48 _{0.34}	54.49 _{0.46}	66.99 _{0.53}
	E-SNLI	ECQA	COMVE	SBIC
UNIFA	67.52 _{0.33}	36.72 _{0.30}	60.97 _{0.64}	65.29 _{0.39}
T5	70.08 _{0.32}	32.38 _{0.30}	49.25 _{0.42}	64.60 _{0.56}

Table 4: A comparison of UNIFIEDQA and T5 when prompted with nearly identical QA_{SIMPLE} and $SQUAD_{T5}$ prompts, respectively. The upper part shows accuracy and the lower part BERTscore. See §3.1 for descriptions of these prompts.

Second, we need to decide whether to add *tags*—a single descriptions of different input elements; e.g., “choice1:” and “choice2:” before the first and second choice in the COMVE input. Without these tags the task seems impossible to understand, but UNIFIEDQA has not been trained with tags for the question, passage, or choices.

Results We present the results of UNIFIEDQA with QA_{SIMPLE} prompts in Table 3. Due to space limits, we report T5’s results with prompts following the SQUAD format for the T5’s pretraining¹⁰ (denoted as $SQUAD_{T5}$) in Table 11 in the Appendix. For ECQA, we report results with the standard UNIFIEDQA format for multiple-choice QA.

We observe that for E-SNLI and COMVE it is crucial to add tags (“premise:”/“hypothesis:”; “choice1:”/“choice2:”). This result is intuitive—it should be difficult to pick one of the two sentences, or classify a relation between them, if sentences are not marked.¹¹ On the other hand, adding choices is not beneficial and in some cases can even decrease the performance. When tags are included, we see that across all the tasks the “What is...?” question performs the best. This also holds for T5 and $SQUAD_{T5}$ prompts (see Table 11). Finally, the prompt with the “What is...?” question and tags in the input outperforms UNIFEW for both tasks UNIFEW can be applied to. This result shows that this prompt is both versatile and effective.

Finally, in Table 4, we compare UNIFIEDQA and T5, with very similar prompts to determine whether the difference between UNIFIEDQA’s

¹⁰“question: *question* context: *paragraph*”

¹¹We speculate that tags do not make difference for “Is...?” questions on COMVE performance because all variations of this prompt perform close to a random baseline. This suggests that the question form hinders the performance.

	E-SNLI	ECQA	COMVE	SBIC
B	75.24 _{0.38}	22.33 _{0.29}	50.36 _{0.31}	61.57 _{0.45}
N	75.09 _{0.45}	27.60 _{0.36}	49.02 _{0.28}	64.66 _{0.52}
	E-SNLI	ECQA	COMVE	SBIC
B	67.66 _{0.35}	19.83 _{0.26}	45.51 _{0.28}	59.18 _{0.46}
N	67.52 _{0.42}	24.52 _{0.32}	44.35 _{0.26}	62.00 _{0.54}

Table 5: A comparison of the basic infilling prompt (B) with its more natural sounding version (N). The upper part shows accuracy and the lower part BERTscore.

and T5’s weights is important for prompting self-rationalization behavior with a QA NL prompt. Specifically, we use the “What is...?” question, include tags, and exclude choices from the input.¹² The only difference is that in case of T5, we add: (ii) “question:” and “context:” in front of the question and input sequence(s), respectively, and (ii) task name (e.g., sensemaking). We make these additions because they are used for SQUAD during T5’s pretraining. See prompts “**SQUAD**_{T5} × WHAT IS...? + TAGS” and “**QA**_{SIMPLE} × WHAT IS...? + TAGS” in Table 2.

For ECQA and COMVE, we observe notable improvements from using UNIFIEDQA, and minor improvements for SBIC. For E-SNLI, T5 is better, presumably because UNIFIEDQA has lost some useful information from MNLI after extensive continued pretraining for QA. These results suggest that UNIFIEDQA is a better model for prompting self-rationalization with QA prompts.

To recap, the outcome of the analysis presented in this section is that QA prompting for inducing self-rationalization behavior is best done when UNIFIEDQA is combined with the NL prompt below. For true QA tasks, we do not add tags.

```
explain what is this/more...? \n
tag1: sequence1 tag2: sequence2 ...</s>
```

3.2 INFILLING Prompts

The simplest way to design an infilling prompt is to prepend the span “<extra_id_0> because <extra_id_1>” to the input. A model should then replace <extra_id_0> with a label/answer and <extra_id_1> with an explanation. Besides being similar to T5’s span infilling pretraining

¹²We do not add the tag “question:” to ECQA for UNIFIEDQA following the original UNIFIEDQA format for multiple-choice QA.

	Task	Accuracy	BERTscore
INFILLING	E-SNLI	75.09 _{0.45}	67.52 _{0.42}
	ECQA	27.60 _{0.36}	24.52 _{0.32}
	COMVE	49.02 _{0.28}	44.35 _{0.26}
	SBIC	64.66 _{0.52}	62.00 _{0.54}
	Average	54.09	49.57
≈T5	E-SNLI	79.21 _{0.29}	71.34 _{0.27}
	ECQA	38.28 _{0.33}	33.91 _{0.29}
	COMVE	55.88 _{0.34}	50.45 _{0.30}
	SBIC	65.06 _{0.60}	62.77 _{0.63}
	Average	59.61	54.62
QA _{SIMPLE}	E-SNLI	75.05 _{0.34}	67.52 _{0.33}
	ECQA	41.37 _{0.34}	36.72 _{0.30}
	COMVE	67.33 _{0.71}	60.97 _{0.64}
	SBIC	67.55 _{0.41}	65.29 _{0.39}
	Average	62.82	57.63

Table 6: A comparison between three prompt types: **INFILLING**, **≈T5**, and **QA_{SIMPLE}** prompts. See §3 for descriptions of these prompts.

task, another benefit of this prompt is that is very flexible—the span above can be added to any task input. This basic infilling prompt could be easily made more natural by prepending phrases such as: “The answer is” (ECQA), “Less common is” (COMVE), or “This is” (E-SNLI, SBIC). We hypothesize that these additional phrases could be beneficial because they suggest which subset of the vocabulary is the right word for filling in <extra_id_0>. We test whether it is beneficial to make the infilling prompt more natural sounding.

Results T5 results are shown in Table 5. The outcome is mixed—while we observe notable benefits for ECQA and SBIC, for E-SNLI and COMVE there is a minor difference in favor of the basic prompt. One way to explain this is that T5 learned about NLI labels from MNLI, so it does not need additional phrase to nudge it in the right direction. COMVE results are comparable to the performance of a random baseline, and the model could not learn the task from the infilling prompt, with or without the additional phrases. Overall, we recommend using the more natural version because it is not detrimental to E-SNLI/COMVE performance while it leads to big improvements for ECQA/SBIC.

3.3 INFILLING vs. \approx T5 vs. QA

We have established appropriate QA and INFILLING prompts in §3.1 and §3.2. We now turn to a comparison between all three prompt types: (i) INFILLING (natural), (ii) \approx T5, and (iii) QA_{SIMPLE} (“What is...?” with tags). The first two are used to prompt T5 and the last type UNIFIEDQA. To construct \approx T5 prompts, for each task in FEB, we identify the most similar T5’s pretraining task (see Table 1) and use that task’s formatting (see, e.g., \approx T5 \times COPA in Table 2).

Results A comparison of the three prompt types is presented in Table 6. The QA_{SIMPLE} prompt outperforms other prompt types for all tasks except E-SNLI for which unsurprisingly \approx T5 is the best.¹³ Finally, this brings us to the end of our extensive exploration of natural language prompts for a prompt-based finetuning approach to few-shot self-rationalization. We identify the QA_{SIMPLE} prompt as the most effective and we use it to study how few-shot self-rationalization performance scales with the size of the UNIFIEDQA model.

4 Improving Self-Rationalization with Increasing Model Size

In §3, we discovered that a QA prompt combined with the base UNIFIEDQA model version (220M parameters) is as an effective combination for few-shot self-rationalization through prompt-based finetuning. In this section, we provide two additional evaluations to establish the first approach to few-shot self-rationalization.

First, we assess how plausible the generated explanations are when evaluated by annotators on Amazon Mechanical Turk. Details of how we conduct human evaluation of plausibility are given in §2. One HIT contains 10 instances and we pay \$1 per HIT.

Next, we investigate how self-rationalization performance changes with the model size since larger pretrained language models often give better few-shot performance (Brown et al., 2020).¹⁴ We wonder whether the same trend will hold for a complex generation task of self-rationalization where it is

¹³To re-iterate, T5 was pretrained with MNLI, and although UNIFIEDQA is based on T5, we speculate that during continued pretraining on 8 QA datasets, it lost some of its original NLI performance.

¹⁴Although sometimes the same might be achieved with less: PET/iPET (Schick and Schütze, 2021b) outperform GPT-3 on SuperGLUE (Wang et al., 2019a) with 32 train examples while requiring only 0.1% GPT-3’s parameters.

```
[Task description]
[Input Type1]: [Input1]
[Input Type2]: [Input2]
Answer: [Label]
Reason: [Explanation]
```

Figure 1: GPT-3 prompt template for all datasets. The strings [Task description], [Input Type1], and [Input Type2] depend on the task. Check Appendix for the detailed prompts.

conceivable that an enormous model could overfit on a few examples. To this end, we evaluate three versions of UNIFIEDQA (BASE, LARGE, 3B) and GPT-3 (Brown et al., 2020).

Experimental Setup GPT-3 cannot be finetuned since its weights are not publicly available. We thus evaluate it using its API and train it using “in-context demonstrations” (Brown et al., 2020). We pack as many training examples (demonstrations) as we can fit in the input sequence, followed by the input of the test example, then run GP-3 to generate its output. The number of demonstrations we are able to fit ranges from [28,45] which are randomly selected from the 48 used for UNIFIEDQA. Since evaluation using a single prompt costs us \$1,050, we do not do prompt search for GPT-3. Instead, we use the template shown in Figure 1 for all datasets.

We re-iterate the main information from §2 here. We report the mean and standard error of the mean accuracy/BERTscore values calculated on 60 dev sets with n examples; $n = 350$ for UNIFIEDQA and $n = 18$ for GPT-3 (because of the API cost). To calculate plausibility, from each out of 60 dev sets with n examples, we take the first $\frac{6}{\# \text{label}}$ correctly predicted examples per label. This gives 360 instances for each model-dataset pair. Each instance is assigned three plausibility scores by three annotators. For each instance, we calculate the mean plausibility score, and report the mean and standard error of the 360 mean plausibility scores. We also report the inter-annotator agreement with Fleiss’ kappa κ .

Ground-truth explanations are evaluated together with explanations generated by four models. Therefore, for GOLD explanations, we report the average of four plausibility scores, standard errors, and κ values calculated with four batches (corresponding to four models).

	Model	# Par.			Plausibility							
					<i>All</i>		<i>Label₁</i>		<i>Label₂</i>		<i>Label₃</i>	
			Accuracy	BERTscore	Score	κ	Score	κ	Score	κ	Score	κ
E-SNLI	BASE	220M	79.21 _{0.29}	71.34 _{0.27}	16.75 _{1.53}	0.73	15.65 _{2.34}	0.67	17.50 _{2.88}	0.79	17.13 _{2.71}	0.72
	LARGE	770M	84.79 _{0.27}	76.56 _{0.27}	32.68 _{1.92}	0.57	27.31 _{2.88}	0.43	33.89 _{3.44}	0.64	36.85 _{3.58}	0.64
	3B	2.8B	87.43 _{0.23}	79.10 _{0.23}	41.60 _{2.08}	0.62	27.13 _{2.85}	0.52	46.76 _{3.84}	0.70	50.92 _{3.63}	0.64
	GPT-3	175B	65.37 _{0.53}	59.83 _{0.47}	42.44 _{2.17}	0.54	27.31 _{2.87}	0.48	66.03 _{4.37}	0.71	43.80 _{3.46}	0.51
	GOLD	-			77.40 _{1.59}	0.63	63.50 _{3.01}	0.44	87.87 _{1.85}	0.74	82.48 _{2.42}	0.72
	RAND	-	33.33									
ECQA	BASE	220M	41.37 _{0.34}	36.72 _{0.30}	25.52 _{1.25}	0.32						
	LARGE	770M	57.19 _{0.36}	51.00 _{0.32}	30.28 _{1.53}	0.38						
	3B	2.8B	65.86 _{0.36}	58.98 _{0.32}	34.23 _{1.56}	0.35						
	GPT-3	175B	60.65 _{1.48}	54.42 _{1.32}	45.06 _{1.44}	0.12						
	GOLD	-			70.88 _{1.47}	0.45						
	RAND	-	20.00									
COMVE	BASE	220M	67.33 _{0.71}	60.97 _{0.64}	13.80 _{1.26}	0.45						
	LARGE	770 M	81.31 _{0.39}	73.95 _{0.36}	25.59 _{1.67}	0.52						
	3B	2.8B	88.96 _{0.38}	81.02 _{0.34}	33.40 _{1.71}	0.63						
	GPT-3	175B	73.98 _{1.40}	67.65 _{1.29}	42.16 _{1.80}	0.73						
	GOLD	-			77.24 _{1.30}	0.55						
	RAND	-	50.00									
SBIC	BASE	220M	67.55 _{0.41}	65.29 _{0.39}	57.96 _{2.25}	0.68	21.36 _{2.06}	0.54	94.57 _{1.08}	0.82		
	LARGE	770M	71.06 _{0.39}	68.55 _{0.39}	61.82 _{2.23}	0.66	27.16 _{2.19}	0.43	96.48 _{0.92}	0.89		
	3B	2.8B	71.66 _{0.48}	68.90 _{0.49}	64.20 _{2.14}	0.68	33.76 _{2.65}	0.55	94.63 _{1.02}	0.81		
	GPT-3	175B	74.17 _{1.41}	71.53 _{1.40}	72.68 _{1.72}	0.53	52.65 _{2.51}	0.34	92.72 _{1.05}	0.72		
	GOLD	-			79.81 _{1.62}	0.67	64.92 _{2.66}	0.52	94.69 _{1.01}	0.81		
	RAND	-	50.00									

Table 7: The first results on the FEB benchmark using T5/UNIFIEDQA (BASE, LARGE, 3b) and GPT-3. T5 with the \approx T5 prompt is used only for E-SNLI, while using UNIFIEDQA with our QA_{SIMPLE} prompt (§3.1) for other datasets. The details of how metrics are calculated are given in §2 and §4. RAND stands for a random baseline and GOLD for human-authored explanations. *Label₁* / *Label₂* / *Label₃* are entailment / neutral / contradiction in E-SNLI and offensive / not_offensive in SBIC.

4.1 Results

Results are shown in Table 7. Note that we use T5 with the \approx T5 prompt for E-SNLI, and UNIFIEDQA with QA_{SIMPLE} (§3) for other datasets to establish the best possible performance for each dataset. We observe that all metrics—accuracy, BERTscore, and plausibility—monotonically increase with the size of UNIFIEDQA for all datasets. That is, larger models learn to predict task labels and generate explanations from a few examples better, despite being overparametrized. UNIFIEDQA-3B has a higher accuracy/BERTscore than GPT-3 for all datasets except SBIC, but GPT-3 generates explanations that are notably more plausible.

The following two observations suggest that few-shot self-rationalization is a promising research direction. The difference in plausibility scores between the BASE and 3B model versions ranges from [6.24, 24.85] (on average 14.85). In other words,

since it is possible to generate more plausible explanation by only increasing the model size, it is conceivable that further progress could be made with more creative approaches. Next, the plausibility score of the best model (GPT-3) ranges from [42.16, 72.68] ([42.16, 52.65] if we only consider SBIC explanations for “offensive” label, i.e., *Label₁*). This results suggests that a moderate plausibility can already be achieved with current models without any additional enhancements.

Despite that, the gap between our best models and human-authored explanations remains large. The average plausibility score across datasets is 43.36 (UNIFIEDQA-3B), 50.58 (GPT-3), and 76.33 (GOLD). In other words, the difference in plausibility scores between UNIFIEDQA-3B’s and human explanations is 32.98, and between GPT-3’s and human explanations is 25.75. We expect that the FEB benchmark, our UNIFIEDQA approach, and first results, present a good starting

point to tackle this challenge.

Performance w.r.t. Labels For E-SNLI and SBIC, we can inspect the metrics with respect to labels. In E-SNLI part of the Table 7, $Label_1$ marks “entailment”, $Label_2$ “neutral”, and $Label_3$ “contradiction”. There are notable differences between the plausibility scores for each label. The plausibility score for “entailment” does not scale with the model size and it is much lower than scores for other labels (the best score is 27.31 vs. 66.03 & 50.92). This issue stems from the difficulty of explaining the entailment label.¹⁵ Even people struggle with explaining “entailment” as evident by the lower GOLD score for “entailment” compared to the other two labels. An interesting observation from the other two labels is that UNIFIEDQA-3B is explains “contradiction” instances best and GPT-3 “neutral” instances.

In SBIC part of the Table 7, $Label_1$ marks “offensive” and $Label_3$ “not offensive” instances. The latter achieve almost perfect plausibility since the models learn to generated “*This post does not imply anything offensive*” for not offensive instances. Thus, main plausibility scores for SBIC are those of offensive instances. We can observe that the relative differences between models for offensive instances are much larger than the relative differences when examples of both labels are counted for (column “All / Score”).

Finally, if we had only looked into a single plausibility score we would not notice these differences. Thus we recommend breaking down the performance with respect to labels whenever possible.

Annotator Agreement Finally, we observe challenges in collecting human judgments of plausibility. For all datasets except ECQA, Fleiss’ κ is either moderate (between 0.41–0.6) or substantial (between 0.61–0.8). One exception is GPT-3 on SBIC ($Label_1$; offensive) where κ is only 0.34. We also observe that κ for GPT-3’s explanations is lower than κ for UNIFIEDQA’s or GOLD explanations, with the exception of COMVE. The most concerning is ECQA where κ is on average 0.35 for UNIFIEDQA’s explanations, 0.34 for GOLD explanations, and only 0.12 for GPT-3’s. Future work should investigate the reasons behind these differences more carefully.

¹⁵Camburu et al.: “We notice that entailment pairs were by far the most difficult to obtain proper explanations for.”

5 Related Work

Self-Rationalization with Few Human-Written Explanations To generate explanations in the form of *highlights* of the input tokens, Lei et al. (2016) introduce a model that selects input tokens and then makes the prediction based solely on them. Such model is trained using only task labels. Since then, many highlighting methods have been designed following their approach (Bastings et al., 2019; Yu et al., 2019; Paranjape et al., 2020). On the other hand, a standard approach to generating free-text explanations is to use human-written explanations (Hendricks et al., 2016; Kim et al., 2018; Hancock et al., 2018; Camburu et al., 2018; Ehsan et al., 2018; Liu et al., 2019; Wu and Mooney, 2019; Narang et al., 2020; Tang et al., 2020; Marasović et al., 2020; Wiegrefe et al., 2021; Kayser et al., 2021). To the best of our knowledge, only two prior works generate *free-text* explanations in a weakly-supervised way from the label/answer prediction loss. Lattinik and Berant (2020) approach commonsense QA in that fashion. Brahman et al. (2021) propose multiple distant supervision approach to explaining a defeasible inference task. In this paper, we introduce the FEB benchmark to unify the evaluation of few-shot self-rationalization and present the first approach and results on FEB.

Few-Shot Learning We study natural language prompts (Brown et al., 2020; Schick and Schütze, 2021a) to establish the first approach to few-shot self-rationalization. Alternatively, in few-shot learning, researchers are studying prompts in the form of continuous (or soft) vectors that do not correspond to real tokens (Qin and Eisner, 2021; Li and Liang, 2021). Such methods present a promising research direction for few-shot self-rationalization. Namely, we show that larger models generate notably more plausible explanations, and “prefix tuning” (Li and Liang, 2021) has been show to learn two condition generation tasks using only 0.1% of the parameters, while maintaining comparable performance. In practice, such approaches still require a notable amount of GPU memory. Thus, any efforts to reduce required memory such as compression (Ganesh et al., 2021) may be valuable for few-shot self-rationalization.

6 Conclusions

We draw attention to the task of few-shot self-rationalization: predicting task labels and gener-

ating *free-text* explanations for the prediction using only a few human-written explanations. We present (i) the FEB benchmark, (ii) the first prompting approach for FEB established through a comprehensive search of natural language prompts, and (iii) results using models with a number of parameters ranging from 110M to 175B. Our human evaluation results show that progress is possible on this task given that just scaling the model size increases both the plausibility of generated explanations and task accuracy by a very large margin. Despite that, few-shot self-rationalization remains very challenging, with plausibility of explanations generated by the best model being 27.75 points behind plausibility of human-authored explanations. We hope that work presented in this paper spurs the community to work on this challenging problem to enable more intuitive interaction with NLP systems.

References

- Shourya Aggarwal, Divyanshu Mandowara, Vishwa-jeet Agrawal, Dinesh Khandelwal, Parag Singla, and Dinesh Garg. 2021. [Explanations for CommonsenseQA: New Dataset and Models](#). In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 3050–3065, Online. Association for Computational Linguistics.
- Tariq Alhindi, Savvas Petridis, and Smaranda Muresan. 2018. [Where is your evidence: Improving fact-checking by justification modeling](#). In *Proceedings of the First Workshop on Fact Extraction and VERification (FEVER)*, pages 85–90, Brussels, Belgium. Association for Computational Linguistics.
- Jasmijn Bastings, Wilker Aziz, and Ivan Titov. 2019. [Interpretable neural predictions with differentiable binary variables](#). In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 2963–2977, Florence, Italy. Association for Computational Linguistics.
- Jonathan Bragg, Arman Cohan, Kyle Lo, and Iz Beltagy. 2021. [Flex: Unifying evaluation for few-shot nlp](#). In *Proceedings of the Advances in Neural Information Processing Systems (NeurIPS)*.
- Faeze Brahman, Vered Shwartz, Rachel Rudinger, and Yejin Choi. 2021. [Learning to rationalize for non-monotonic reasoning with distant supervision](#). In *Proceedings of the AAAI Conference on Artificial Intelligence*.
- Tom Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared D Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel Ziegler, Jeffrey Wu, Clemens Winter, Chris Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. 2020. [Language models are few-shot learners](#). In *Advances in Neural Information Processing Systems*, volume 33, pages 1877–1901. Curran Associates, Inc.
- Oana-Maria Camburu, Tim Rocktäschel, Thomas Lukasiewicz, and Phil Blunsom. 2018. [e-SNLI: Natural language inference with natural language explanations](#). In *Proceedings of the Advances in Neural Information Processing Systems (NeurIPS)*.
- Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. 2019. [BERT: Pre-training of deep bidirectional transformers for language understanding](#). In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, Minneapolis, Minnesota. Association for Computational Linguistics.
- Upol Ehsan, Brent Harrison, Larry Chan, and Mark O Riedl. 2018. [Rationalization: A neural machine translation approach to generating natural language explanations](#). In *Proceedings of the 2018 AAAI/ACM Conference on AI, Ethics, and Society*.
- Prakhar Ganesh, Yao Chen, Xin Lou, Mohammad Ali Khan, Yin Yang, Hassan Sajjad, Preslav Nakov, Deming Chen, and Marianne Winslett. 2021. [Compressing Large-Scale Transformer-Based Models: A Case Study on BERT](#). *Transactions of the Association for Computational Linguistics*, 9:1061–1080.
- Tianyu Gao, Adam Fisch, and Danqi Chen. 2021. [Making pre-trained language models better few-shot learners](#). In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 3816–3830, Online. Association for Computational Linguistics.
- Matt Gardner, Jonathan Berant, Hannaneh Hajishirzi, Alon Talmor, and Sewon Min. 2019. [Question answering is a format; when is it useful?](#) arXiv:1909.11291.
- Braden Hancock, Paroma Varma, Stephanie Wang, Martin Bringmann, Percy Liang, and Christopher Ré. 2018. [Training classifiers with natural language explanations](#). In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1884–1895, Melbourne, Australia. Association for Computational Linguistics.
- Lisa Anne Hendricks, Zeynep Akata, Marcus Rohrbach, Jeff Donahue, Bernt Schiele, and Trevor

- Darrell. 2016. [Generating visual explanations](#). In *European Conference on Computer Vision (ECCV)*.
- Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021. [Measuring massive multitask language understanding](#). In *The International Conference on Learning Representations (ICLR)*.
- Zhengbao Jiang, Frank F. Xu, Jun Araki, and Graham Neubig. 2020. [How can we know what language models know?](#) *Transactions of the Association for Computational Linguistics*, 8:423–438.
- Jared Kaplan, Sam McCandlish, Tom Henighan, Tom B. Brown, Benjamin Chess, Rewon Child, Scott Gray, Alec Radford, Jeff Wu, and Dario Amodei. 2020. [Scaling laws for neural language models](#). arXiv:2001.08361.
- Maxime Kayser, Oana-Maria Camburu, Leonard Salewski, Cornelius Emde, Virginie Do, Zeynep Akata, and Thomas Lukasiewicz. 2021. [e-vil: A dataset and benchmark for natural language explanations in vision-language tasks](#). In *Proceedings of the IEEE/CVF International Conference on Computer Vision (ICCV)*.
- Daniel Khashabi, Sewon Min, Tushar Khot, Ashish Sabharwal, Oyvind Tafjord, Peter Clark, and Hannaneh Hajishirzi. 2020. [UNIFIEDQA: Crossing format boundaries with a single QA system](#). In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 1896–1907, Online. Association for Computational Linguistics.
- Jinkyu Kim, Anna Rohrbach, Trevor Darrell, John Canny, and Zeynep Akata. 2018. [Textual explanations for self-driving vehicles](#). In *Proceedings of the European conference on computer vision (ECCV)*.
- Najoung Kim, Ellie Pavlick, Burcu Karagol Ayan, and Deepak Ramachandran. 2021. [Which linguist invented the lightbulb? presupposition verification for question-answering](#). arXiv:2101.00391.
- Neema Kotonya and Francesca Toni. 2020. [Explainable automated fact-checking for public health claims](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 7740–7754, Online. Association for Computational Linguistics.
- Veronica Latcinnik and Jonathan Berant. 2020. [Explaining question answering models through text generation](#). arXiv:2004.05569.
- Tao Lei, Regina Barzilay, and Tommi Jaakkola. 2016. [Rationalizing neural predictions](#). In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 107–117, Austin, Texas. Association for Computational Linguistics.
- Xiang Lisa Li and Percy Liang. 2021. [Prefix-tuning: Optimizing continuous prompts for generation](#). In *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing (Volume 1: Long Papers)*, pages 4582–4597, Online. Association for Computational Linguistics.
- Wang Ling, Dani Yogatama, Chris Dyer, and Phil Blunsom. 2017. [Program induction by rationale generation: Learning to solve and explain algebraic word problems](#). In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 158–167, Vancouver, Canada. Association for Computational Linguistics.
- Hui Liu, Qingyu Yin, and William Yang Wang. 2019. [Towards explainable NLP: A generative explanation framework for text classification](#). In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 5570–5581, Florence, Italy. Association for Computational Linguistics.
- Ana Marasović, Chandra Bhagavatula, Jae sung Park, Ronan Le Bras, Noah A. Smith, and Yejin Choi. 2020. [Natural language rationales with full-stack visual reasoning: From pixels to semantic frames to commonsense graphs](#). In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 2810–2829, Online. Association for Computational Linguistics.
- David Alvarez Melis and Tommi Jaakkola. 2018. [Towards robust interpretability with self-explaining neural networks](#). In *Proceedings of the Advances in Neural Information Processing Systems (NeurIPS)*.
- Sharan Narang, Hyung Won Chung, Yi Tay, Liam Fedus, Thibault Fevry, Michael Matena, Karishma Malkan, Noah Fiedel, Noam Shazeer, Zhenzhong Lan, Yanqi Zhou, Wei Li, Nan Ding, Jake Marcus, Adam Roberts, and Colin Raffel. 2021. [Do transformer modifications transfer across implementations and applications?](#) In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 5758–5773, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Sharan Narang, Colin Raffel, Katherine Lee, Adam Roberts, Noah Fiedel, and Karishma Malkan. 2020. [WT5?! Training Text-to-Text Models to Explain their Predictions](#). arXiv:2004.14546.
- Bhargavi Paranjape, Mandar Joshi, John Thickstun, Hannaneh Hajishirzi, and Luke Zettlemoyer. 2020. [An information bottleneck approach for controlling conciseness in rationale extraction](#). In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 1938–1952, Online. Association for Computational Linguistics.
- Guanghui Qin and Jason Eisner. 2021. [Learning how to ask: Querying LMs with mixtures of soft prompts](#). In *Proceedings of the 2021 Conference of the North*

- American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 5203–5212, Online. Association for Computational Linguistics.
- Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. [Exploring the limits of transfer learning with a unified text-to-text transformer](#). *Journal of Machine Learning Research*, 21(140):1–67.
- Nazneen Fatema Rajani, Bryan McCann, Caiming Xiong, and Richard Socher. 2019. [Explain yourself! leveraging language models for commonsense reasoning](#). In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4932–4942, Florence, Italy. Association for Computational Linguistics.
- Pranav Rajpurkar, Jian Zhang, Konstantin Lopyrev, and Percy Liang. 2016. [SQuAD: 100,000+ questions for machine comprehension of text](#). In *Proceedings of the 2016 Conference on Empirical Methods in Natural Language Processing*, pages 2383–2392, Austin, Texas. Association for Computational Linguistics.
- Melissa Roemmele, Cosmin Adrian Bejan, and Andrew S. Gordon. 2011. [Choice of plausible alternatives: An evaluation of commonsense causal reasoning](#). In *AAAI Spring Symposium Series*.
- Cynthia Rudin, Chaofan Chen, Zhi Chen, Haiyang Huang, Lesia Semenova, and Chudi Zhong. 2021. [Interpretable machine learning: Fundamental principles and 10 grand challenges](#). arXiv: 2103.11251.
- Maarten Sap, Saadia Gabriel, Lianhui Qin, Dan Jurafsky, Noah A. Smith, and Yejin Choi. 2020. [Social bias frames: Reasoning about social and power implications of language](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 5477–5490, Online. Association for Computational Linguistics.
- Timo Schick and Hinrich Schütze. 2021a. [Exploiting cloze-questions for few-shot text classification and natural language inference](#). In *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pages 255–269, Online. Association for Computational Linguistics.
- Timo Schick and Hinrich Schütze. 2021b. [It’s not just size that matters: Small language models are also few-shot learners](#). In *Proceedings of the 2021 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies*, pages 2339–2352, Online. Association for Computational Linguistics.
- Zheng Tang, Gus Hahn-Powell, and Mihai Surdeanu. 2020. [Exploring interpretability in event extraction: Multitask learning of a neural event classifier and an explanation decoder](#). In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics: Student Research Workshop*, pages 169–175, Online. Association for Computational Linguistics.
- Alex Wang, Yada Pruksachatkun, Nikita Nangia, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R. Bowman. 2019a. [Superglue: A stickier benchmark for general-purpose language understanding systems](#). In *Proceedings of the Advances in Neural Information Processing Systems (NeurIPS)*.
- Cunxiang Wang, Shuailong Liang, Yue Zhang, Xiaonan Li, and Tian Gao. 2019b. [Does it make sense? and why? a pilot study for sense making and explanation](#). In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4020–4026, Florence, Italy. Association for Computational Linguistics.
- Alex Warstadt, Amanpreet Singh, and Samuel R. Bowman. 2019. [Neural network acceptability judgments](#). *Transactions of the Association for Computational Linguistics*, 7:625–641.
- Sarah Wiegreffe and Ana Marasović. 2021. [Teach me to explain: A review of datasets for explainable nlp](#). In *Proceedings of the Advances in Neural Information Processing Systems (NeurIPS)*.
- Sarah Wiegreffe, Ana Marasović, and Noah A. Smith. 2021. [Measuring association between labels and free-text rationales](#). In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pages 10266–10284, Online and Punta Cana, Dominican Republic. Association for Computational Linguistics.
- Adina Williams, Nikita Nangia, and Samuel Bowman. 2018. [A broad-coverage challenge corpus for sentence understanding through inference](#). In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pages 1112–1122, New Orleans, Louisiana. Association for Computational Linguistics.
- Jialin Wu and Raymond Mooney. 2019. [Faithful multimodal explanation for visual question answering](#). In *Proceedings of the 2019 ACL Workshop BlackboxNLP: Analyzing and Interpreting Neural Networks for NLP*, pages 103–112, Florence, Italy. Association for Computational Linguistics.
- Fan Yang, Mengnan Du, and Xia Hu. 2019. [Evaluating explanation without ground truth in interpretable machine learning](#). 1907.06831.
- Mo Yu, Shiyu Chang, Yang Zhang, and Tommi Jaakkola. 2019. [Rethinking cooperative rationalization: Introspective extraction and complement control](#). In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages

4094–4103, Hong Kong, China. Association for Computational Linguistics.

Sheng Zhang, Xiaodong Liu, Jingjing Liu, Jianfeng Gao, Kevin Duh, and Benjamin Van Durme. 2018. [Record: Bridging the gap between human and machine commonsense reading comprehension](#). arXiv:1810.12885.

Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q. Weinberger, and Yoav Artzi. 2020. [Bertscore: Evaluating text generation with bert](#). In *The International Conference on Learning Representations (ICLR)*.

A Appendix

GPUs	NVIDIA A100 on Google Cloud
Implementation	https://github.com/allenai/feb
Hyperparameter	Assignment
max step number	300
batch size	4 (1 for UNIFIEDQA-3B)
gradient accumulation steps	1 (4 for UNIFIEDQA-3B)
learning rate	3e-5
learning rate scheduler	linear
warmup steps	0
decoding	greedy

Table 8: Hyperparameters used in our experiments.

		Accuracy	BERTscore
COS-E	INFILLING (b)	34.28 _{0.36}	29.60 _{0.32}
	INFILLING (n)	40.14 _{0.38}	34.70 _{0.34}
	≈T5	51.69 _{0.41}	44.56 _{0.36}
	SQUAD _{T5}	51.15 _{0.34}	44.13 _{0.29}
	QA _{SIMPLE}	59.96 _{0.32}	48.57 _{0.26}

Table 9: A comparison of all prompt types introduced in §3 on COS-E.

	Size	Accuracy	BERTscore
COS-E	BASE	58.32 _{0.28}	50.43 _{0.25}
	LARGE	69.44 _{0.30}	60.11 _{0.26}
	3B	75.37 _{0.31}	65.34 _{0.28}
	GPT-3	68.43 _{1.35}	59.48 _{1.18}

Table 10: The effect of scaling the UNIFIEDQA model size on self-rationalization of COS-E.

	Prompt	Accuracy	BERTscore
E-SNLI	Is...?	38.68 _{0.44}	34.74 _{0.40}
	+ tags	48.20 _{0.62}	43.22 _{0.58}
E-SNLI	What is...?	60.76 _{0.85}	54.75 _{0.77}
	+ tags	77.86 _{0.34}	70.08 _{0.32}
ECQA	UNIFIEDQA	36.48 _{0.34}	32.38 _{0.30}
	RANDOM BASELINE	20.00	-
COMVE	Is...?	50.38 _{0.16}	45.54 _{0.14}
	+ tags	50.17 _{0.14}	45.35 _{0.13}
COMVE	What is...?	50.54 _{0.21}	45.67 _{0.19}
	+ tags	54.49 _{0.46}	49.25 _{0.42}
SBIC	Is...?	63.37 _{0.58}	61.15 _{0.57}
	+ tags	63.82 _{0.54}	61.69 _{0.55}
SBIC	What is...?	66.67 _{0.49}	64.33 _{0.51}
	+ tags	66.99 _{0.53}	64.60 _{0.56}

Table 11: A comparison between SQUAD_{T5} prompts with “Is...?” and “What is...?” questions. See §3.1 for more info. We also inspect the effects of adding answer choices and *tags* to the input. Tags are a single word descriptions of the input elements; e.g., E-SNLI’s tags are “premise:” / “hypothesis:” before premise / hypothesis.

```

===== SBIC =====
Is the following post offensive? and why?
Post: [Input]
Answer: Yes|No
Reason: [Explanation]

===== E-SNLI =====
Answer the question and provide a reason why
the answer is correct.
[Premise]
Question: Is [Hypothesis]?
Answer: Yes|No|Maybe
Reason: [Explanation]

===== ECQA =====
Answer the question from the provided
choices, and provide a reason why the answer
is correct.
Question: [Question]
Choices: [Choices]
Answer: [one of the choices]
Reason: [Explanation]

===== ComVE =====
Which of the two choices makes more sense?
and why?
Choice1: [Choice1]
Choice2: [Choice2]
Answer: Choice1|Choice2
Reason: [Explanation]

```

Figure 2: GPT-3 prompt templates for all datasets